

35 SIZES
AVAILABLE

15"-22"
RIM SIZE

Q
SPEED RATING

NEXEN
NEXEN TIRE

Inch	Product Code	Size	Load Index & Speed Symbol	Ply Rating	Max. Air psi	Max. Load (lbs)		Rim		Section Width inch	Overall Diameter inch	Tread Depth /32"	Sidewall	
						S	D	Measuring	Approved					
15	15867	33X12.50R15	108	Q	6	35	2,205	-	10.0	8.5-11.0	12.5	32.8	21.0	Black
	15871	35X12.50R15	113	Q	6	35	2,535	-	10.0	8.5-11.0	12.5	34.8	21.0	Black
16	15873	LT265/75R16	123/120	Q	10	80	3,415	3,085	7.5	7.0-8.0	10.5	31.9	19.0	Black
	15879	LT285/75R16	126/123	Q	10	80	3,750	3,415	8.0	7.5-9.0	11.3	33.1	19.0	Black
17	15883	LT235/80R17	120/117	Q	10	80	3,085	2,835	6.5	6.0-7.5	9.3	32.0	18.0	Black
	15884	LT245/75R17	121/118	Q	10	80	3,195	2,910	7.0	6.5-7.5	9.8	31.7	18.0	Black
	15886	LT255/75R17	111/108	Q	6	50	2,405	2,205	7.0	6.5-8.5	10.0	32.3	18.0	Black
	15887	LT265/70R17	121/118	Q	10	80	3,195	2,910	8.0	7.0-8.5	10.7	31.9	19.0	Black
	15713	LT285/70R17	121/118	Q	10	80	3,195	2,910	8.5	7.5-9.0	11.0	33.0	19.0	Black
	15888	LT295/70R17	121/118	Q	10	80	3,195	2,910	8.5	7.5-10.0	11.8	33.5	20.0	Black
	16398	LT305/65R17	121/118	Q	12	80	3,195	2,910	9.0	8.5-11.0	12.2	32.8	20.0	Black
	16399	LT315/70R17	121/118	Q	12	80	3,195	2,910	9.5	8.0-11.0	12.7	34.6	20.0	Black
	16261	33X12.50R17	121	Q	12	80	3,195	-	10.0	8.5-11.0	12.5	32.8	21.0	Black
	16262	35X12.50R17	121	Q	12	80	3,195	-	10.0	8.5-11.0	12.5	34.8	21.0	Black
18	16348	37X12.50R17	121	Q	12	80	3,195	-	10.0	8.5-11.0	12.5	36.8	21.0	Black
	15925	LT275/65R18	123/120	Q	10	80	3,415	3,085	8.0	7.5-9.0	11.0	32.3	19.0	Black
	15897	LT275/70R18	125/122	Q	10	80	3,640	3,305	8.0	7.0-8.5	11.0	33.4	19.0	Black
	15926	LT285/65R18	125/122	Q	10	80	3,640	3,305	8.5	8.0-10.0	11.5	32.8	19.0	Black
	15898	LT295/70R18	129/126	Q	10	80	4,080	3,750	8.5	7.5-10.0	11.8	34.5	20.0	Black
	16400	LT305/70R18	128/125	Q	12	80	3,970	3,640	9.0	8.5-10.0	12.2	35.1	20.0	Black
	16263	33X12.50R18	122	Q	12	80	3,305	-	10.0	8.5-11.0	12.5	32.8	21.0	Black
20	16264	35X12.50R18	128	Q	12	80	3,970	-	10.0	8.5-11.0	12.5	34.8	21.0	Black
	15929	LT275/65R20	126/123	Q	10	80	3,750	3,415	8.0	7.5-9.5	11.0	34.3	19.0	Black
	15932	LT285/55R20	122/119	Q	10	80	3,305	3,000	9.0	8.0-10.0	11.7	32.6	19.0	Black
	15933	LT295/55R20	123/120	Q	10	80	3,415	3,085	9.5	8.0-10.0	12.2	33.0	20.0	Black
	15931	LT295/60R20	126/123	Q	10	80	3,750	3,415	8.5	8.0-10.0	11.8	34.2	20.0	Black
	15930	LT295/65R20	129/126	Q	10	80	4,080	3,750	8.5	8.0-10.0	11.8	35.4	20.0	Black
	16271	LT305/55R20	125/122	Q	12	80	3,640	3,305	9.5	8.5-11.0	12.4	33.5	20.0	Black
	16265	33X12.50R20	119	Q	12	80	3,000	-	10.0	8.5-11.0	12.5	32.8	21.0	Black
	16266	35X12.50R20	125	Q	12	80	3,640	-	10.0	8.5-11.0	12.5	34.8	21.0	Black
22	16267	37X12.50R20	128	Q	12	80	3,970	-	10.0	8.5-11.0	12.5	36.8	21.0	Black
	16401	37X13.50R20	128	Q	12	80	3,970	-	11.0	8.5-11.0	13.6	36.8	21.0	Black
	16270	37X13.50R22	128	Q	12	80	3,970	-	11.0	8.5-11.0	13.6	36.8	21.0	Black
	16269	35X12.50R22	121	Q	12	80	3,195	-	10.0	8.5-11.0	12.5	34.8	21.0	Black
16268	33X12.50R22	114	Q	12	80	2,600	-	10.0	8.5-11.0	12.5	32.8	19.0	Black	



**EXTREME OFF-ROAD.
TOWING CAPACITY.
DURABILITY.**





WE GOT YOU.

ALL NEW MUD TERRAIN TIRE

ROADIAN MTX

NEXEN NEXEN TIRE

NEXEN TIRE AMERICA INC. Corporate Headquarters, 21073 Pathfinder Rd., Ste. 100, Diamond Bar, CA 91765

T: (909) 923-4011 F: (909) 923-3991 E: info@nexentireusa.com NexenTireUSA.com |    

ROADIAN MTX

ON AND OFF THE TRAIL ... WE GOT YOU.

THE ROADIAN MTX FROM NEXEN TIRE FEATURES AN AGGRESSIVE DESIGN THAT IS EXTREMELY VERSATILE FOR ON- AND OFF-ROAD DRIVING. THE TIRE'S CONSTRUCTION IS DESIGNED TO MAXIMIZE LOAD AND TOWING CAPABILITIES WITHOUT SACRIFICING ANY OF THE RUGGED TRAITS OR ON-HIGHWAY DRIVING COMFORT ONE WOULD EXPECT FROM OUR ROADIAN LINE OF TIRES.



DUAL SIDEWALLS

All Roadian MTXs come with two unique sidewall designs!



3-PLY SIDEWALLS

On all sizes for peace of mind!



F-LOAD RANGE

12-ply and 80 psi ready!

45-DAY FREE TRIAL

You'll love it! Otherwise exchange it for a different set of Nexen Tires, no charge!

